


# RCP6(S)-WSA10C



| Model Specification Items | Series  | Type | Encoder Type              | Motor Type                     | Lead   | Stroke                                   | Applicable Controller/I/O Type                                | Cable Length  | Options                                  |
|---------------------------|---|------|---------------------------|--------------------------------|--|--|---|---|--|
|                           | WSA10C  | WA   | 35P                       |                                |  |  |   |   |  |
|                           | RCP6: Separate Controller<br>RCP6S: Built-in Controller |      | WA: Battery-less Absolute | 35P: Stepper Motor<br>35□ Size | 16: 16mm<br>10: 10mm<br>5: 5mm<br>2.5: 2.5mm | 50: 50mm<br>500: 500mm (50mm increments) | [RCP6]<br>P3: PCON<br>MCON<br>MSEL<br>[RCP6S]<br>SE: SIO Type | N : None<br>P : 1m<br>S : 3m<br>M : 5m<br>X□ : Specified Length<br>R□ : Robot Cable | Please refer to the options table below. |

\* RCP6 does not include a controller. RCP6S includes a built-in controller.  
\* Please refer to P.10 for more information about the model specification items.





\*Depending on the model, there may be some limitations to using the vertical, side, and ceiling mount positions. Please contact IAI for more information regarding mounting positions.



- POINT Selection Notes**
- (1) The maximum acceleration/deceleration is 1G for horizontal, and 0.5G for vertical use.
  - (2) The actuator specification displays the payload's maximum value, but it will vary depending on the acceleration and speed. Please refer to the "Selection Guidelines" (RCP6 Tables of Payload by Speed/Acceleration) on P.115 for more details.
  - (3) When performing push-motion operation, please confirm the push force of each model by checking the "Correlation diagram of push force and current limit" on P.113.

### Correlation Diagrams of Speed and Payload



## Actuator Specifications

### Lead and Payload

| Model Number                      | Lead (mm) | Connected Controller | Max. Payload    |               | Stroke (mm)                                 |
|-----------------------------------|-----------|----------------------|-----------------|---------------|---|
|                                   |           |                      | Horizontal (kg) | Vertical (kg) |   |
| RCP6(S)-WSA10C-WA-35P-16-①-②-③-④  | 16        | High-output Enabled  | 4               | -             | 50~500<br>(The increment of stroke is 50mm) |
| RCP6(S)-WSA10C-WA-35P-10-①-②-③-④  | 10        | High-output Enabled  | 15              | -             |   |
| RCP6(S)-WSA10C-WA-35P-5-①-②-③-④   | 5         | High-output Enabled  | 28              | 3             |   |
| RCP6(S)-WSA10C-WA-35P-2.5-①-②-③-④ | 2.5       | High-output Enabled  | 40              | 10            |   |

### Stroke and Max. Speed

(Unit: mm/s)

| Lead (mm) | Connected Controller | Max. Speed          |              |          |          |          |
|-----------|----------------------|---------------------|--------------|----------|----------|----------|
|           |                      | 50~300 (Every 50mm) | 350 (mm)     | 400 (mm) | 450 (mm) | 500 (mm) |
| 16        | High-output Enabled  | 840                 |              |          | 775      | 660      |
| 10        | High-output Enabled  | 610                 | 590          | 490      | 415      |          |
| 5         | High-output Enabled  | 390<br><350>        | 355<br><350> | 290      | 245      | 205      |
| 2.5       | High-output Enabled  | 195<br><175>        | 175          | 145      | 120      | 100      |

Legend: ① Stroke ② Applicable controller/I/O type ③ Cable length ④ Options  
Values in brackets < > are for vertical use.

### ① Stroke

| Stroke (mm) | RCP6 | RCP6S | Stroke (mm) | RCP6 | RCP6S |
|-------------|------|-------|-------------|------|-------|
| 50          | ○    | ○     | 300         | ○    | ○     |
| 100         | ○    | ○     | 350         | ○    | ○     |
| 150         | ○    | ○     | 400         | ○    | ○     |
| 200         | ○    | ○     | 450         | ○    | ○     |
| 250         | ○    | ○     | 500         | ○    | ○     |

### ④ Options

| Name                           | Option Code | Reference Page |
|--------------------------------|-------------|----------------|
| Brake                          | B           | See P.105      |
| Cable exit direction (Top)     | CJT         | See P.105      |
| Cable exit direction (Right)   | CJR         | See P.105      |
| Cable exit direction (Bottom)  | CJB         | See P.105      |
| High-precision specification * | HPR         | See P.108      |
| Non-motor end specification    | NM          | See P.110      |

\* Positioning repeatability is ±5µm for high-precision specification (HPR).  
High-precision specification option cannot be selected for lead 16.  
# When selecting multiple options, please list them in alphabetical order. (e.g. B-CJB-NM)

### ③ Cable Length

| Cable Type       | Cable Code           | RCP6 | RCP6S |
|------------------|----------------------|------|-------|
| Standard         | P (1m)               | ○    | ○     |
|                  | S (3m)               | ○    | ○     |
|                  | M (5m)               | ○    | ○     |
| Specified Length | X06 (6m) ~X10 (10m)  | ○    | ○     |
|                  | X11 (11m) ~X15 (15m) | ○    | ○     |
|                  | X16 (16m) ~X20 (20m) | ○    | ○     |
|                  | R01 (1m) ~R03 (3m)   | ○    | ○     |
| Robot Cable      | R04 (4m) ~R05 (5m)   | ○    | ○     |
|                  | R06 (6m) ~R10 (10m)  | ○    | ○     |
|                  | R11 (11m) ~R15 (15m) | ○    | ○     |
|                  | R16 (16m) ~R20 (20m) | ○    | ○     |

\* Please refer to P.144 for more information regarding the maintenance cables.

### Actuator Specifications

| Item                               | Description                                     |
|------------------------------------|---|
| Drive system                       | Ball screw φ8mm, rolled C10                     |
| Positioning repeatability (*1)     | ±0.01mm [±0.005mm]                              |
| Lost motion                        | 0.1mm or less                                   |
| Base                               | Material: Aluminum with white alumite treatment |
| Static allowable moment            | Ma: 271N·m, Mb: 271N·m, Mc: 553N·m              |
| Dynamic allowable moment (*2)      | Ma: 65.4N·m, Mb: 65.4N·m, Mc: 134N·m            |
| Ambient operating temp. & humidity | 0~40°C, 85% RH or less (Non-condensing)         |




\* Reference for overhang load length: Ma: 500mm or less, Mb, Mc: 500mm or less  
(\*1) Values in [ ] are for high-precision (for lead 2.5/5/10) specification.  
(\*2) Assumes a standard rated life of 5,000km. The service life will vary depending on operation and installation conditions.  
Please refer to our website for more information regarding the directions of the allowable moment and overhang load length.

Dimensions

CAD drawings can be downloaded from our website.  
www.intelligentactuator.com



\*1 When the slider is returning to its home position, please be careful of interference from surrounding objects, as it will travel until it reaches the M.E.  
M.E: Mechanical end S.E: Stroke end



■ Dimensions and Mass by Stroke

|           |       | Stroke    | 50  | 100 | 150 | 200 | 250 | 300 | 350 | 400 | 450 | 500 |
|-----------|-------|-----------|-----|-----|-----|-----|-----|-----|-----|-----|-----|-----|
| L         | RCP6  | w/o brake | 422 | 472 | 522 | 572 | 622 | 672 | 722 | 772 | 822 | 872 |
|           |       | w/ brake  | 452 | 502 | 552 | 602 | 652 | 702 | 752 | 802 | 852 | 902 |
|           | RCP6S | w/o brake | 452 | 502 | 552 | 602 | 652 | 702 | 752 | 802 | 852 | 902 |
|           |       | w/ brake  | 467 | 517 | 567 | 617 | 667 | 717 | 767 | 817 | 867 | 917 |
| A         |       |           | 293 | 343 | 393 | 443 | 493 | 543 | 593 | 643 | 693 | 743 |
| G         |       |           | -   | -   | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 |
| H         |       |           | 156 | 206 | 56  | 106 | 56  | 106 | 56  | 106 | 56  | 106 |
| J         |       |           | 0   | 0   | 1   | 1   | 2   | 2   | 3   | 3   | 4   | 4   |
| K         |       |           | 4   | 4   | 8   | 8   | 10  | 10  | 12  | 12  | 14  | 14  |
| N         |       |           | -   | -   | 100 | 100 | 100 | 100 | 100 | 100 | 100 | 100 |
| P         |       |           | 1   | 1   | 2   | 2   | 2   | 2   | 2   | 2   | 2   | 2   |
| Q         |       |           | -   | -   | 206 | 256 | 306 | 356 | 406 | 456 | 506 | 556 |
| R         |       |           | 0   | 0   | 1   | 1   | 1   | 1   | 1   | 1   | 1   | 1   |
| Mass (kg) | RCP6  | w/o brake | 2.9 | 3.1 | 3.4 | 3.6 | 3.8 | 4.1 | 4.3 | 4.6 | 4.8 | 5.0 |
|           |       | w/ brake  | 3.1 | 3.3 | 3.6 | 3.8 | 4.0 | 4.3 | 4.5 | 4.8 | 5.0 | 5.2 |
|           | RCP6S | w/o brake | 3.0 | 3.2 | 3.5 | 3.7 | 3.9 | 4.2 | 4.4 | 4.7 | 4.9 | 5.1 |
|           |       | w/ brake  | 3.1 | 3.4 | 3.6 | 3.9 | 4.1 | 4.3 | 4.6 | 4.8 | 5.1 | 5.3 |

② Applicable Controllers

The RCP6 series actuators can be operated by the controllers indicated below. Please select the type depending on your intended use. \* Please refer to P.147 for more information about the built-in controller of RCP6S series.

| Name        | External view | Max. number of controlled axes | Input power             | Control method                         |             |         |   | Maximum number of positioning points | Reference page                     |
|-------------|---------------|--------------------------------|-------------------------|--|-------------|---------|---|--------------------------------------|------------------------------------|
|             |               |                                |                         | Positioner                             | Pulse train | Program | Network *Option   |                                      |                                    |
| PCON-CB/CGB |               | 1                              | DC24V                   | ● *Option                              | ● *Option   | -       |   | 512<br>(768 for network spec.)       | Please see P.131                   |
| MCON-C/CG   |               | 4                              |                         | This model is network-compatible only. |             |         |   |                                      | 256                                |
| MSEL-PC/PG  |               | 4                              | Single-phase 100~230VAC | -                                      | -           | ●       | Note:<br>The type of compatible networks will vary depending on the controller.<br>Please refer to reference page for more information. | 30,000                               | Please see the MSEL-PC/PG catalog. |

\* Please select "high-output specification" as an option for the MCON. With the MCON, operation is possible only when the high-output specification is selected.